



NKJ-C6TWHI1B21

CAT6 UTP Tool-less Keystone Jack

FEATURES

- RJ45 8P 8C 180° 50u Punch Down Jack
- Terminating 4 pairs, 22-26 AWG Cable
- Universal labels color coded for T568A and T568B wiring schemes
- Fitting high density keystone panel

SPECIFICATIONS

1. RJ45 Jack:
Housing: PC, UL 94V-0, with optional color
Contact Bracket: PC, UL 94V-0, transparent
2. RJ45 Jack Contact:
Material: Phosphor Bronze with Nickel Plated
Finish: 50 micro-inch Gold Plated on plug contact area
3. IDC:
Housing: PC, UL 94V-0
Terminal: Phosphor Bronze, Tin Plated
4. IDC CAP: PC, UL 94V-0

PERFORMANCE

- T568A & T568B wiring sticker
- Insertion force: 20N max (IEC 60603-7-4)
- Retention strength : 7.7 kg between jack and plug
- Operation temperature : 0 to 60C (ISO/IEC 11801, ANSI/TIA/EIA 568 C.2)
- Life (Mating Cycles):
Jack: 750 cycle min (ISO/IEC 11801, IEC 60603-7-4)
- IDC: suitable for 22-26 AWG stranded and solid wire,
- The Cat6 transmission performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard

Product No.	Description	Color
NKJ-C6TWHI1B21	UTP Cat.6 Tooless Keystone Jack	White

ABS: Acrylonitrile Butadiene Styrene