

# Product datasheet

Specifications



APC Easy UPS On-Line, 3kVA/  
2400W, Rackmount 4U, 230V, 6x  
IEC C13 + 1x IEC C19 outlets,  
Intelligent Card Slot, LCD,  
Extended Runtime, W/ rail kit

SRV3KRILRK

## Overview

**Presentation** High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

**Lead time** Usually in Stock

## Main

**Main Input Voltage** 230 V

**product or component type** Uninterruptible power supply (UPS)

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated power in W** 2400 W

**Rated power in VA** 3000 VA

**Input Connection Type** IEC 60320 C20

**output connection type** 6 IEC 60320 C13  
1 IEC 60320 C19

**Number of rack unit** 4U

**Number of cables** 1

**Provided equipment** 1 IEC 60320 C19 to Schuko power cable  
1 IEC 60320 C13 to C14 power cable  
1 USB cable  
1 RS-232 configuration cable  
2 rack mounting brackets  
2 rack mounting support rails  
1 external battery pack  
1 battery cable

**Range of product** Easy UPS On-Line

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Battery type** Lead-acid battery

**Battery voltage** 72 V

**Number of battery filled slots** 1

**Number of battery free slots** 0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Battery recharge time	5.5 h
Battery life	3...5 year(s)
Battery charger power	350 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black (RAL 7010)
Height	17.2 cm
Width	43.7 cm
Depth	63.2 cm
Net weight	52 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting position	Horizontal

## Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	CE UKCA EAC TISI
------------------------	---------------------------

<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...3000 m
<b>Ambient air temperature for storage</b>	-20...50 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0...15000 m
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	910 Btu/h
<b>IP degree of protection</b>	IP20

## Communications & Management

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Control panel</b>	Multifunction LCD status and control console

## Surge Protection and Filtering

<b>Surge energy rate</b>	600 J
--------------------------	-------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	3
<b>Package 1 Height</b>	48 cm
<b>Package 1 Width</b>	60 cm
<b>Package 1 Length</b>	70 cm
<b>Package 1 Weight</b>	66.8 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)

Image of product / Alternate images

Alternative

---



