

16-Port Gigabit Unmanaged PoE Switch with 2 SFP Ports

Technical Specifications

General

Network Interface	<ul style="list-style-type: none"> • 16 10/100/1000Mbps PoE RJ45 port (port 1 ~port 16) • 2 Gigabit SFP Ports 	
Transmission Rate	<ul style="list-style-type: none"> • 10/100/1000Mbps Each port supports MDI / MDIX auto-flip auto-negotiation 	<ul style="list-style-type: none"> • Network interface: 10BASE-T or 100BASE-TX, 1000 BASE-T Ethernet RJ-45 port
Protocols and Standards	<ul style="list-style-type: none"> • IEEE802.3 10 BASE-T • IEEE 802.3u 100 BASE-TX • ANSI/IEEE 802.3 NWay auto-negotiation 	<ul style="list-style-type: none"> • IEEE802.3ab 1000 BASE-T • IEEE802.3z 1000 BASE-X • IEEE802.3x Flow Control • IEEE 802.3af/at standard

Functionality

Switching Capacity	<ul style="list-style-type: none"> • 52 Gbps 	
Packet Forwarding	<ul style="list-style-type: none"> • 38.688Mpps 	
LED's Indicator PoE	<ul style="list-style-type: none"> • Power 	<ul style="list-style-type: none"> • LINK/ACT, PoE
Budget	<ul style="list-style-type: none"> • 250W 	
Power	<ul style="list-style-type: none"> • 100-240VAC, 50-60Hz 	

Physical

Physical Characteristics	<ul style="list-style-type: none"> • Dimensions (LxWxH): 320*180*44mm • Weight: 2.314kg 	
Environmental Parameter	<ul style="list-style-type: none"> • Operating Temperature: 0 to 40 °C (32 to 104 °F) 	
	<ul style="list-style-type: none"> • Operating Humidity: 10% to 90% non-condensing 	

Order Information

<i>Part Number</i>	<i>Description</i>
DGS-F1016P	16-Port 10/100/1000 Mbps Unmanaged PoE Switch with 2 SFP Ports