


6-Port Gigabit Desktop Switch with 3-Port PoE+ and 1-Port PoE++

MODEL: TL-SG1006PP Datasheet



Highlights

- With 3 PoE+ and 1 PoE++ ports, transfers data and power on one single cable
- Working with IEEE 802.3af/at/bt compliant PDs, expands your network
- Supports PoE power up to 60 W for PoE++ port and 30 W for each PoE+ port
- Supports PoE power up to 64 W* for all PoE ports
- Up to 250 m data and power transmission under Extend Mode** specially designed for surveillance system
- With PoE Auto Recovery, the switch will automatically reboot your dropped or unresponsive PoE-powered devices connected to port 1-4
- Requires no configuration and installation
- Fanless Design
- Supports desktop and wall mountable installation methods

Overview

TL-SG1006PP is an unmanaged switch with 6 Gigabit ports that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af/at/bt compliant Powered Devices (PDs) at port 1 and IEEE 802.3af/at compliant Powered Devices (PDs) at port 2-4. In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Power Over Ethernet

4 RJ45 ports (port 1 to port 4) of the switch support Power over Ethernet (PoE) function. They can automatically detect and supply power with those IEEE 802.3af/at/bt compliant Powered Devices (PDs) at port 1 and IEEE 802.3af/at compliant Powered Devices (PDs) at port 2-4.

Overload Arrangement

TL-SG1006PP has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is ≥ 64 W*, a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.

Intelligent Power Management

Priority (port 1 > port 2 > port 3 > port 4): This function will help protect the system when the system power is overloaded. For example, port 2, 3, and 4 is using 18 W respectively (maximum power per port is 30 W); the system power is 54 W in total. If there is an additional PD inserted to port 1 with 25 W, and then the system will cut off the power of port 4 because of the overloaded power, this means port 2 and 3 will use 18 W respectively and port 1 will use 25 W, no power will be supplied to port 4.

Highlight Performance


- Up to 250 m PoE power supply and data transmission under Extend Mode** for port 1-2.
- With PoE Auto Recovery, the switch will constantly detect the data transmission with PoE-powered devices (PD) for port 1-4. When the switch finds that a PD stops sending data packets to the switch for a long period, the switch will reboot it automatically.

Easy to Use

TL-SG1006PP is easy to install and use. It requires no configuration and installation. With desktop and wall mountable design, outstanding performance and quality, the TP-Link 6-Port Gigabit Desktop Switch with 3-Port PoE+ and 1-Port PoE++ TL-SG1006PP is a great selection for expanding your network.

Specifications

Hardware Features & Performance

Product Picture	
Model	TL-SG1006PP
Standards	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Network Ports	6 10/100/1000 Mbps RJ45 Ports;
Network Media (Cable)	10BASE-T: UTP category 3, 4, 5 cable (maximum 100 m); EIA/TIA-568 100Ω STP (maximum 100 m) 100BASE-TX: UTP category 5, 5e cable (maximum 100 m); EIA/TIA-568 100Ω STP (maximum 100 m) 1000BASE-T: UTP category 5e cable or above (maximum 100 m); EIA/TIA-568 100Ω STP (maximum 100 m)
PoE	PoE Standard: IEEE 802.3af/at/bt for port 1, IEEE 802.3af/at for port 2-4 PoE Port 1: up to 60 W PoE Port 2-4: up to 30 W per port PoE Power Budget: 64 W*
Auto-Negotiation	YES
Auto MDI/MDIX	YES
PoE Power on RJ45	Port 1: Power+: pin 3 & pin 6 Power -: pin 1 & pin 2 Power+: pin 4 & pin 5 Power -: pin 7 & pin 8 Port 2-4: Power+: pin 3 & pin 6 Power -: pin 1 & pin 2
Max Power Consumption	4.75 W (220 V/50 Hz no PD connected) 71.46 W (220 V/50 Hz with 64 W* PD connected)
Max Heat Dissipation	16.20 BTU/h (220 V/50 Hz no PD connected) 243.68 BTU/h (220 V/50 Hz with 64 W* PD connected)
Forwarding Mode	Store and Forward
Switch Capacity	12 Gbps
MAC Address Table	4K, Auto-learning, Auto-aging
Extend Mode	YES (for Ports 1-2)
PoE Auto Recovery	YES (for Ports 1-4)
Flow Control	YES
Fanless	YES
LED	Power, Link/Act, PoE Status, PoE MAX
Dimensions	6.2x4.0x1.0 in (158x101x25 mm)
Certification	CE, FCC
Environment	Operating Temperature: 0°C to 40°C (32°F to 104°F) Storage Temperature: -40°C to 70°C (-40°F to 158°F) Operating Humidity: 10% to 90% RH, non-condensing Storage Humidity: 5% to 90% RH, non-condensing

Note:

* PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

**The speed of the ports which are under extend mode will be downgraded to 10Mbps. Actual transmission distance may vary from the quality of the cables.

www.tp-link.com

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2023 TP-Link