

16-Port Gigabit Unmanaged PoE Switch with 2 SFP Ports

Technical Specifications	
General	
Network Interface	• 16 10/100/1000Mbps PoE RJ45 port (port 1 ~port 16) • 2 Gigabit SFP Ports
Transmission Rate	• 10/100/1000Mbps Each port supports MDI / MDIX auto-flip auto-negotiation • Network interface: 10BASE-T or 100BASE-TX, 1000 BASE-T Ethernet RJ-45 port
Protocols and Standards	• IEEE802.3 10 BASE-T • IEEE 802.3u 100 BASE-TX • ANSI/IEEE 802.3 NWay auto-negotiation • IEEE802.3ab 1000 BASE-T • IEEE802.3z 1000 BASE-X • IEEE802.3x Flow Control • IEEE 802.3af/at standard
Functionality	
Switching Capacity	• 52 Gbps
Packet Forwarding	• 38.688Mpps
LED's Indicator PoE	• Power • LINK/ACT, PoE
Budget	• 250W
Power	• 100-240VAC, 50-60Hz
Physical	
Physical Characteristics	• Dimensions (LxWxH): 320*180*44mm • Weight: 2.314kg
Environmental Parameter	• Operating Temperature: 0 to 40 °C (32 to 104 °F)
	• Operating Humidity: 10% to 90% non-condensing
Order Information	
Part Number	Description
DGS-F1016P	16-Port 10/100/1000 Mbps Unmanaged PoE Switch with 2 SFP Ports