

Product datasheet

Specifications



APC Easy Rack PDU, Basic, 0U, 1 Phase, 3.7kW, 230V, 16A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1116B

⚠ To be discontinued

⚠ Discontinued on: 1 Dec 2025

⚠ To be end-of-service on: 30 Sep 2028

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|---|
| Colour | Black |
| Product or component type | PDU |
| PDU type | Basic |
| Cord length | 2.99 m |
| Number of cables | 1 |
| Provided equipment | Installation guide Toolless mounting kit Vertical mounting brackets |

Complementary

| | |
|--------------------------|-------------------------------------|
| Input Voltage | 200 V 208 V 230 V |
| Height | 902 mm |
| Width | 62 mm |
| Output Voltage | 230 V |
| Depth | 44.4 mm |
| Net weight | 2.2 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Input Plug Type | IEC 60309 16 A 2P + E |
| Mounting mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Input current limits | 16 A |
| Load capacity | 3680 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 20 IEC 60320 C13 4 IEC 60320 C19 |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environment

| | |
|---------------------------------------|--------------|
| Product certifications | CE TÜV |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...15240 m |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 132 cm |
| Package 1 Width | 11 cm |
| Package 1 Length | 16 cm |
| Package 1 Weight | 2.98 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 12 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 56 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 0.2 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 45 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.2 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACH Regulation | Free of Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|---|
| Recyclability potential, in % | 45 |
| End of life manual availability | End of Life Information |
| Take-back | Nej |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |