


Long Range Bluetooth USB Adapter













Highlights

High-Performance Antenna for a Powerful Bluetooth Signal

Stable Connection, Further Coverage. One powerful signal-boosting
High-performance antenna greatly extends existing Wi-Fi coverage, offering
wireless communication with Bluetooth-enabled devices from farther away.



Connect with Multiple Devices via Bluetooth 5.3

UB500 Plus supports advanced Bluetooth 5.3 and enables wireless connectivity with a wide range of devices such as computers, printers, phones, headsets, speakers, keyboards, controllers, etc.



Features



· Bluetooth 5.3 – Backward compatible with Bluetooth 5.2/5.0/4.0 devices



· Adjustable, Multi-Directional Antenna – Rotate and adjust the multi-directional antenna to improve user experience and performance in different environments.



- Versatile Wireless Connectivity Enable wireless communication with Bluetooth-enabled computers, printers, phones, headsets, speakers, keyboards and more
- BLE Technology Bluetooth Low Energy technology for energy-saving wireless connectivity
- · Broad Operation Range Enjoy stable connection via your Bluetooth headset with a long transmission distance in open space



For more

For more information, please visit

https://www.tp-link.com/products/details/?model=UB500+Plus_V1

or scan the QR code left

©2024 TP-Link

For support and warranty, please visit: http://www.tp-link.com/support

[†]To ensure compatibility after an OS update, you may need to update the adapter's drivers. Check the full list of supported OS at tp-link.com/download-center.

Specifications

Hardware

· Standard: Bluetooth 5.3

· Interface: USB-A

· Dimensions: 3.19 × 1.65 × 0.66 in (81 × 42 × 16.8 mm)

· Antenna: 1× External High-Performance Antenna

· Transmit Power: 10dBm (CE) (EIRP)

Others

· Package Contents

Long Range Bluetooth USB Adapter UB500 Plus

Quick Installation Guide

· System Requirements

Supported operating systems include Win 11/10/8.1/7⁺

· Environment

Operating Temperature: 0°C~40°C (32°F~104°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing