

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 32A, 230V, (20)C13 & (4)C19

AP7553

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	200 V 208 V 230 V
Height	1619 mm
Width	56 mm
Output Voltage	230 V
Depth	44 mm
Net weight	5.57 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	32 A
Load capacity	7400 VA
Network frequency	47...63 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product certifications	CE VDE
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	15.000 cm
Package 1 Length	212.000 cm
Package 1 Weight	8.943 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	120.000 cm
Package 2 Length	222.000 cm
Package 2 Weight	101.700 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 476 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	0.5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 452 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
Halogen-free status	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

